



FA 10 211 00

P. 1 | 2




①



②













③



● Sternal | ● Dorsal ● Lateral



<b>HS CODE</b>
63079098
<b>CARTON SIZE / PCS.</b>
60 X 40 X 24 cm / 12
<b>AET (EU) N°2777/10362-04/E05-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>AET (UKCA) N°AB0321/16083-01/E02-01</b>
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>MODULE D 11 IN14/14003</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 10 211 00
SIZES	TU
 KG	MAX. 140 KG (VG 11.062 – Rev. 6 - 07/2018)
CE	EN 361:2002, EN 358:2018, ISO 9150, ISO 15025
Attachment	Dorsal (A), Sternal (A), Lateral
	2 / 4
MAT.  / 	
MAT.  45 mm	Aramid
 /  / 	3 / 0 / 0
	2.55 KG



**Taille** Poids maxi utilisateur  
**Size** Max. user weight  
**Tamaño** Peso máximo del usuario  
**Dimensione** Peso massimo dell'utente  
**Größe** Höchstgewicht des Benutzers



**Nombre de boucles de réglage / boucles automatiques**  
 Number of adjustment buckles / automatic buckles  
**Cantidad de hebillas de ajuste / hebillas automáticas**  
 Numero di fibbie di regolazione / fibbie autobloccanti  
**Anzahl der Einstellschnallen / Schnellverschluss-Schnallen**



**Matière des / boucles**  
 Material of rings / buckles  
**Material de anillas en D / hebillas**  
 Materia del D / Fibbie  
**Material D-Ringe/Schnallen**



**Nombre de dés porte-outils / poignées porte-matériel / triangles porte-accessoires**  
 Number of tool-holding D-rings/equipment-holding handles/accessory-holding triangles  
**Cantidad de anillas en D portaherramientas / asas portamateriales / triángulos portaccesorios**  
 Numero di portautensili / maniglie portamateriale / triangoli portaccessori  
**Anzahl der Werkzeug-D-Ringe / Werkzeug-Halteringe / Zubehör-Triangel**



**Sangle pouvant résister jusqu'à des températures maximales de 371°C**  
 Strap that can withstand temperatures up to 371°C  
**Correa que puede resistir temperaturas máximas de hasta 371°C**  
 Cinghie possono resistere alle temperature di massimo 371°C  
**Gurt hitzeresistent bis maximal 371°C**



**Sangle pouvant résister à des projections de métal en fusion**  
 Strap that can withstand splashes of molten metal  
**Correa que puede resistir proyecciones de metal en fusión**  
 Cinghie possono resistere alle proiezioni di metallo in fusione  
**Gurt beständig gegen Spritzer von Schmelzmetall**