



MultisafeWay








Ø 23.0 mm

240.0 mm



HS CODE
7610 90 10
CARTON SIZE / PCS.
34 X 34 X 34 cm / 1
Certificate of test SPC0223656/1414 Issue 3 Extension 1
Satra Technology Centre, N° 0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ACKNOWLEDGEMENT OF RECEIPT N°1120/1/2020
Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika


REF.	FA 60 022 01
CE	EN 795:2012 Type A
	---
	---
MAT.	
	M16 (X4)
R (kN) / MBS (kN)	---
+	ATEX Directive 2014/34/EU, Machinery Directive 360° Rotation (8 positions)
	11.28 KG



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer



Charge maxi admissible
Max. allowable load
Carga máxima admisible
Peso massimale
Zulässige Höchstlast



Fixations à utiliser
Fasteners to use
Fijaciones que deben usarse
Elementi di fissaggio da utilizzare
Zu verwendende Befestigungen