

## INSULATION BLANKETS

### Description

CEPRO insulation blankets are used for the controlled cooling of welded products.

### Application

The maximum application temperature is 550 °C, shortly up to 600°C.

### Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check insulation products for tears and or other damage. Replace damaged blankets where necessary.
- Insulation products can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether a specific insulation product is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO insulation products are sewn on the cut edges with best quality Kevlar thread.
- All of our insulation products have the following thermal conductivity coefficient per layer of 25mm = 0,044 W/m\*K by 100 °C (More technical details are available upon request).

### Characteristics

CEPRO insulation blankets are built up from several different heat resistant and insulating products

### Available dimensions

100 x 200cm, thickness 3cm	<b>57.50.23.10</b>
200 x 200cm, thickness 3cm	<b>57.50.23.20</b>
100 x 200cm, thickness 6cm	<b>57.50.26.10</b>
200 x 200cm, thickness 6cm	<b>57.50.26.20</b>



### Overview layers CEPRO insulation blanket

